





Material	P24	P36	P40	P60	P80	P100	P120	P150	P180	P240	P320	P400	P600	P800	P1200
KX167	•	•	•	•	•	•	•	•	•	•	•	•	•		
GXK51	•	•	•	•	•	•	•	•	•		•	•	•		
GXK51-ZQ		•	•	•	•	•	•	•	•	•	•	•	•		
JT133				•	•	•	•	•	•	•	•	•			
JB5				•	•	•	•	•	•	•	•	•			
BYC81	•	•	•	•	•	•	•	•	•	•	•	•	•		
KX456	•	•	•	•	•	•	•	•	•	•	•				
KX663		•	•	•	•		•								
115.03-B		•		•	•		•								
KY533Z		•	•	•	•		•								
TS790Y	•	•	•	•		•	•								
COMPACT							•	•	•	•	•	•	•	•	•
ENGINEERED									A100			A45		A30	A16
CORK												•	•	•	

## **Coated Abrasives Rolls Specification**

Material	Grain	Backing	Special Features	Application
KX163	AlO3	XY PC	WP HT	For heavy duty wood, metal, stainless, chrome and general. Can be used in oil and coolant.
GXK51	AlO3	X PC	NASS	For general medium to light duty wood, plastic, metal and light stainless applications.
GXK51-ZQ	AlO3	ХС		Used for the production of flap wheels and specialty abrasives. Wood, plastics, metals and stainless
JT133	AlO3	J PC	WR	For general flexible grinding and polishing applications. Wood, metal, plastic and stainless. Crank polishing
JB5	AlO3	J C		For general hand operations. Used to slit into handy rolls.
BYC81	SiC	ΥP	WP HT	For heavy duty non-ferrous applications. Glass, wood, stainless and masonry. Segmented wide belts.
KX456	SiC	X PC	WP	For med and light duty non-ferrous applications. Glass, wood, stainless and masonry.
KX663	Zir/AlO3	ХС	WP	For medium duty metal, hard wood and stainless applications.
115.03-B	Zir/AlO3	ΧP	WP	For heavy duty metal, hard metal and stainless steel applications. Extra sharp edge.
KY533Z	Zir/AlO3	ΥP	WP HT	For heavy duty metal, hard metal and stainless steel applications. Top size for grain ripping and grain preservation.
TS790Y	Ceramic	ΥP	WP HT	For heavy duty metal, hard metal and stainless steel applications. Top size for grain ripping applications and grain preservation.
COMPACT	AlO3	ΥP	WP HT	Multi layered grain. Self sharpening. For med grinding and polishing applications. Metal, hard metals and stainless steel.
ENGINEERED	AlO3	X PC		Multi layered grain. Self sharpening structured grain. For med grinding and polishing applications. Metal, hard metals and stainless steel. Can be used wet.
CORK	SiC	X PC	WP	For non-ferrous, glass, masonry and stainless steel polishing. Can be used wet.