

Quick-Loc Coated Discs



Santek Quick-Loc Discs are used for grinding, dressing, deburring, polishing and blending of metal surfaces.

Small and flexible, Quick-Loc discs prove highly effective for stock removal and blending of surfaces in both general and tight spaces.

Available with an option of a plastic male or a female metal, thread button.



Safety



Quick-Loc Discs perform best between 20-30m/s, this giving the optimum balance between stock removal, surface finish, cutting temperature and wheel life.

NB! Excess speed is dangerous and may result in product disintegration, grain shedding and overheating.

NEVER USE QUICK-LOC DISCS AT SPEEDS IN EXCESS OF 40m/s!

Do not use wet or in any coolant or oil.

Use in accordance to ANSI B7.1.

Standard Sizes Available

Diameter	Alox Brown	Zir Blue	Zir Green	SiC Black	Ceramic Orange
30mm		•	•	•	
50mm	•	•	•	•	•
75mm		•	•	•	•



Disc Holder



Standard Grit Sizes Available

Type	Grit	P36	P60	P80	P120	P150	P240	P320	P400	P600
Alox Brown		•	•	•	•	•	•	•	•	•
Zir Blue		•	•	•	•					
Zir Green		•	•	•	•					
SiC Black		•	•	•	•	•	•	•	•	•
Cer. Orange		•	•	•	•					

